Butt connectors, insulated, 0.5 - 1.0 mm² (43965), 100 pieces



Increases your process reliability: Consistently high processing quality for lasting contact reliability.
Facilitates handling: Easy and fast cable insertion thanks to funnel sleeve.
Increases your safety: High heat resistance of up to 105° C.
Saves time: no further insulation required after crimping.
Application: Ideal for connecting grounding cables. Suitable for use in control cabinet construction, for cable assembly or also in the construction of rail vehicles as well as in the CarHifi sector.
When connecting electrical conductors, a secure connection is essential. In combination with the automatic crimping tools and connectors from Wiha, a gas-tight connection can be made, thus ensuring long-term contact reliability. The conical collar makes it easier to insert the stranded wire into the sleeve during installation. Wiha's halogen-free connectors have a heat resistance of up to 105° C. They are manufactured according to the dimensional specifications of DIN 46341.
For electrical applications
- Blister packaging: No
- ESD Article: No
- Content: 100
- Color: red
- Diameter D1: 4.1 mm
- Diameter D2: 1.6 mm
- Length L1: 26 mm
- Nominal size min (mm^2): 0.5 mm^2
- Nominal size max (mm^2): 1.0 mm^2
- Nominal size (min - max) (mm^2): 0.5 - 1 mm^2
- Stripping range (min - max) (AWG): 22 - 16
- Stripping range min. (AWG): 22
- Stripping range max. (AWG): 16
- with battery: No

Item no.	WL72795
Alternative article name	C101X005010
Manufacturer	WIHA
Manufacturer article no.	43965
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Sales unit	1 piece
Content unit	100 piece
Product series	C101
VDE	no
ESD compliant	no
Packaging dimensions	piece