

TorqueVario®-S electric torque screwdriver set 0.8-5.0 Nm PlusMinus/Pozidriv 5 pcs. variably adjustable torque limitation (38074)

Increases your efficiency: the right torque protects you from material damage and rework.

Reduces your costs: The right torque protects you from warranty claims.

Offers you full protection: Each tool individually tested at 10,000 V AC and approved for 1,000 V AC.

Increases your safety: Wiha slimBits ensure good and protected access to low-lying screws.

Protects your health: With patented SoftFinish® handle design for work that is gentle on hands and muscles. Recommended by doctors and therapists of the AGR!

Meets your demands: Variable adjustable torque covers wide range of applications.

Application: For controlled screwing in the area of live parts up to 1,000 V AC.

Standards: Tested according to IEC 60900.

The fully certified TorqueVario®-S VDE torque system offers controlled screw tightening and at the same time safety in electrical applications. The tool set includes an ergonomically designed torque screwdriver handle with integrated numerical scale, 2 slimBits, a bit holder and the setting tool. All components are conveniently and clearly arranged in a high-quality and durable box. The torque screwdriver VDE covers a wide range of applications with its variably adjustable torque range of 0.8-5.0 Nm. A clearly audible and tactile signal when the torque is triggered ensures a process-safe torque mechanism that protects against material damage and rework. With a triggering accuracy of +/- 6%, the torque tool meets the requirements of DIN EN ISO 6789. The insulated ClicFix bit holder ensures a secure hold of the 75 mm long slimBits by means of a mechanical blade lock. Both the torque screwdriver and the slimBits are subjected to routine testing in accordance with the international IEC 60900 standard and enable safe working on live parts up to 1,000 V AC.

For electrical applications

DIN EN ISO 6789.

Contents:

1x TorqueVario®-S electric torque screwdriver variably adjustable torque limitation 0.8 - 5 (26626).

1x Adjustment tool for torque screwdriver with longitudinal handle 90mm (26864)

1x Adapter TorqueVario-S electric for slimBits 6.0mm (35870)

1x Bit slimBit electric PlusMinus/Pozidriv SL/PZ1 x 75mm (34589)

1x Bit slimBit electric PlusMinus/Pozidriv SL/PZ2 x 75mm (34590)

• Blister packaging: No

- ESD Article: No
- with battery: No

item number	WL72868
Alternative item description	XX2872S3
manufacturer	WIHA
manufacturer item number	38074
GPSR manufacturer information	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
order unit	1 piece
content unit	1 piece
standards	Tested according to IEC 60900, DIN EN ISO 6789.
product series	2872
VDE	yes
type of screw	mixed
ESD safe	no
packaging mass	set
type of screwdriver	torque screwdriver