

Safeguard electric field meter in an ESD case



The SafeGuard electric field meter guarantees precise measurements for maximum protection against electrostatic discharge (ESD) thanks to its high-quality components and conductive polymer casing. At the upper end of the device is a star-shaped influence electrode, at a short distance in front of this rotates a modulation impeller of the same star shape, which is connected to ground. The influence electrode is enclosed by a ring electrode system which serves as mechanical protection for the modulation impeller and the field plate. The display on the front panel is a 2x 12-digit alphanumeric LCD display. The unit is supplied in a high-quality and sturdy ESD carrying case with foam insert - for easy stowage and safe transport.

- Type of measurement: Influence principle (field mill principle).
- Conversion of the measured field strength over the set measuring distance into the charge in volts
- "One-button" operation
- Very high zero point stability: Necessary adjustment before each measurement is not necessary (compared to other systems)

- Permanent battery voltage monitoring with automatic shutdown
- Two-line, 12-digit alphanumeric LCD display
- Adjustment accuracy: < 5%
- Output voltage (only with man. E-field measurement): $\pm 1V$ ($R_i > 1k\Omega$)
- Operating mode: battery operation
- Operating time: approx. 10h with alkaline battery
- Measuring range: 0 to ± 200 kV (distance mode), 0 - 1 MV/m (field strength mode)
- Output: $\pm 1V$ ($R_i > 1k\Omega$) proportional to the measured field strength (only in "E-Field Measurement" mode)
- Standard measuring distance: 2cm

item number	WL73730
Alternative item description	Safeguard SFM PRO ZBS
manufacturer	KW-SG
manufacturer item number	SFM PRO ZBS
GPSR manufacturer information	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
scope of supply	<ul style="list-style-type: none"> • Electric field meter (EFM) from SafeGuard • ESD case with foam insert • 2x 9V NiMH rechargeable batteries • Plug-in charger for 9V-battery • Coiled cable with tap terminal • Instruction manual • Calibration certificate
order unit	1 piece
content unit	1 piece
display type	digital
range	0 to ± 200 kV (distance mode), 0 - 1 MV/m (field strength mode)
ESD safe	yes