

Rod light TANEО TND 1400/950/D - 23 W / 1500 lm



The TANEО can be described in one sentence "ALL-ROUND TALENT FOR WORKING WITH OPTIMUM LIGHT". It creates optimal working conditions in production, assembly and quality assurance.

Arm-mounted luminaires provide large-area, bright and, above all, precisely adjustable lighting in machines, workshops, laboratories and assembly workplaces.

- Mounting: LED
- Control gear: Electronic ballast
- Connected load: 100-240 V; 50/60 Hz
- Power consumption: approx. 23 W
- Luminaire luminous flux: 1500 lm
- Luminaire luminous efficacy: 65 lm/W
- Light color: Neutral white, approx. 5000 K
- Color rendering (Ra): ≥ 90
- Color tolerance: 3 SDCM
- Protection class: IP 20

Products for the electronic industry



- Protection class: I with plug-in power supply; III without plug-in power supply
- Operation: multifunctional pushbutton
- Luminaire housing
- Color: Aluminum colors (colorless anodized)
- Lamp cover: plastic, structured
- Luminaire frame
- Color: Silver metallic
- Weight (net): approx. 1.9 kg
- Power cord: 3.40 m power plug CEE 7/VII
- Mounting: base, table clamp (accessory), spigot16

item number	WL73751
manufacturer	WALDMANN
manufacturer item number	113735000-00809726
order unit	1 piece
content unit	1 piece
Colour	silver
Lamp or magnifier type	rod light
luminous flux	1500 lm
Protection class	IP 20
connections	100-240 V; 50/60 Hz
dimnable	no
colour temperature	5000 °K
power	23 W
equipping	LED
attachment	Table clamp
ESD safe	no