

## Smart Ultra soldering and desoldering tweezers WXUTS set, RTWUS 015 B / WSR 210



- Smart Ultra soldering and desoldering tweezers set including WXUTS desoldering tweezers
- 150 W, 24 V
- Unique 2-in-1 desoldering tweezers, 150 W, 12 V: Supports high power desoldering applications
- Quick desoldering tweezer change: Active Tip Cartridge System allows you to easily change the soldering tip even with a hot desoldering tweezer, without the need for an additional tool or adjustment.
- Maximum Protection: Military standard, Mil-Spec compliant and fully compliant with IPC industry standards (IPC - TM-650 2.5.33 Measurement of Electrical Overstress from Soldering Hand Tools)
- Visual process control through RGB signal function: easy identification of tools. Color matching possible. (Choose between 12 colors)

- Integrated parameter memory: Standby temperature and automatic shutdown time can be easily stored in the soldering iron; parameters only need to be stored once; desoldering tweezers can use them with any WXsmart station.
- Ergonomics: improved comfort and safe handling with new ergonomic soft grips.
- Connectable to: WXsmart control unit; WSR 210 safety rest; RTWUS desoldering iron range.
- Highest precision in soldering process due to short distance between tip and handle and optimized tip design; Precise positioning due to unique parallel sliding block guide; No alignment after tip change due to paired design (pre-aligned tips > time saving > increases productivity); Adjustment functions with Allen key: 1.5 mm possible if required ( $\pm 80^\circ$  rotation angle adjustment + vertical length adjustment of  $\pm 1.2\text{mm}$ ); Intelligent desoldering tweezers tips (allows automatic tip offset)
- High performance / high productivity: Extremely short heat-up time: 10 sec.; Excellent response time.

Item no.	WL74122
Model	WXUTS SET
Manufacturer	WELLER
Manufacturer article no.	T0051321399
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Length with packaging	318 mm
Width with packaging	170 mm
Height with packaging	155 mm
Scope of delivery	1x WXUTS 1x RTWUS 015 B 1x WSR 210
Sales unit	1 piece
Content unit	1 piece
Power	150 W
Voltage	24 V
Heating time	10 s
Temperature range °C	100 – 450 °C
Temperature range °F	200 – 850 °F
Shape of soldering tip	double tip