

System luminaire TAMETO - SAHQ 66 R - 26 W / 2300 lm



TAMETO is available with state-of-the-art T5 fluorescent lamp technology or the latest LED technology. The system luminaire also offers various options for mounting.

System luminaires are ideal for workplace-related lighting of industrial workplaces.

Depending on the type and structure of the workplace, the luminaire modules are used individually or in combination.

- Mounting: LED
- Control gear: Electronic ballast
- Connected load: 220-240 V; 50/60 Hz
- Power consumption: approx. 26 W
- Luminaire luminous flux: 2300 lm
- Luminaire luminous efficacy: 88 lm/W
- Light color: Neutral white, approx. 4000 K
- Color rendering (Ra): ≥ 90
- Protection class: IP 20
- Protection class: I

- Technique: Continuously dimmable
- Operation: Rocker switch
- Luminaire housing
- Material: Aluminum/plastic
- Surface: Anodized
- Color: Aluminum colors (colorless anodized)
- Lamp cover: Plastic, Structured
- Weight (net): approx. 5.1 kg
- Power cord: 3.00 m power plug CEE 7/VII
- Design: Surface mounted version
- Mounting: Screw-on bracket
- glare control: cone prism diaphragm

Item no.	WL74689
Manufacturer	WALDMANN
Manufacturer article no.	112976000-00551352
GPSR manufacturer data	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
Sales unit	1 piece
Content unit	1 piece
Colour	silver
Material	aluminum/plastic
Incl. battery	no
Light source	LED
Lamp or magnifying glass type	system light
Luminous flux	2300 lm
Protection class	IP 20
Connection values	220-240 V; 50/60 Hz
Dimmable	yes
Colour temperature	4000 °K
Power	26 W
ESD compliant	no