

Guide kit for SFR-B, Ø 1,6 mm, 0,5 m, with solder wire perforation



The Guide Kit GSFR is designed to be used with the Solder Feeder SFR in automatic soldering processes. It's compatible with solder wire diameters of Ø 1,6 - 1,63 mm. This Guide Kit suits for the SFR Solder Feeder and its easily exchangeable if different solder wire diameters are used. Guide Kits are also available without solder wire perforation and for other wire diameters. Different guide lengths are available if SFR is not fixed on the robot soldering head, check the manual for detailed information.

Item no.	WL83188
Model	GSFR16V05-B
Model line	SFR-B
Manufacturer	JBC
Manufacturer article no.	GSFR16V05-B
GPSR manufacturer data	JBC Soldering SL Ramón y Cajal 3 ES-08750 Molins De Rei

Products for the electronic industry



	www.jbctools.com
Length	500 mm
Length with packaging	245 mm
Width with packaging	185 mm
Height with packaging	45 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Perforation	yes
Wire diameter	1.6 mm
ESD compliant	yes
Wire diameter	1.6 – 1.63 mm

Other versions

Item no.	Length	Wire diameter
WL83165	300 mm	0.8 mm
WL83170	300 mm	1 mm
WL83176	300 mm	1.2 mm
WL83180	300 mm	1.5 mm
WL83186	300 mm	1.6 mm
WL83181	400 mm	1.5 mm
WL83166	500 mm	0.8 mm
WL83171	500 mm	1 mm
WL83177	500 mm	1.2 mm
WL83182	500 mm	1.5 mm
WL83188	500 mm	1.6 mm
WL83167	600 mm	0.8 mm
WL83172	600 mm	1 mm
WL83168	700 mm	0.8 mm
WL83173	700 mm	1 mm
WL83178	700 mm	1.2 mm
WL83183	700 mm	1.5 mm
WL83169	800 mm	0.8 mm
WL83174	1000 mm	1 mm

Products for the electronic industry



WL83179	1000 mm	1.2 mm
WL83184	1000 mm	1.5 mm
WL83175	1500 mm	1 mm
WL83185	1500 mm	1.5 mm
WL83189	1500 mm	1.6 mm