Urethane - Clear 5 Liter, 5 Lit.



The ECS urethane polyurethane varnish in 5 liters is an extremely resistant protective and insulating varnish, specially developed for electronics. It is characterized by its excellent insulating properties and offers high surface and volume resistances as well as good dielectric strength. Thanks to its low dielectric constant and loss factors, it guarantees reliable performance. The transparent varnish is resistant to moisture, diluted acids and alkalis. With its elasticity, abrasion and adhesion resistance, it ensures good long-term adhesion in the temperature range from -40°C to +120°C. Chemical cross-linking takes place during the drying process, which means that the varnish offers optimum protection even under damp or aggressive conditions.

- Particularly resistant protective and insulating varnish for electronics
- URETHANE-CLEAR is a transparent, air-drying, one-component polyurethane varnish with excellent insulating properties
- It offers high surface and volume resistance, good dielectric strength, low dielectric constant and loss factors
- URETHANE-CLEAR is resistant to moisture, diluted acids and alkalis

• The paint is elastic, abrasion and adhesive resistant. It has permanently good adhesion in the temperature range from -40° C to +120° C.
• During the drying period, the paint chemically crosslinks, so that it provides excellent protection even in damp or aggressive environmental conditions
• Contents: 5 Liter

Item no.	**WL83864**
Manufacturer	ECS
Manufacturer article no.	771.L05.000
GPSR manufacturer data	ECS AG Talstrasse 35 CH-8808 Päffikon www.ecsag.com
Sales unit	1 piece
Content unit	1 piece
ESD compliant	no