

Thinner Urethane 1 Liter, 1 Lit.



The ECS thinner for urethanes is the ideal product for achieving the right consistency for your paints. With a mixing ratio that varies depending on the application, you can adjust the flow behavior according to your wishes. For optimum spray application, we recommend a ratio of 1:1 to achieve a uniform result with thin coats. If you want thicker coats, simply use 3 parts concentrate and 1 part thinner. Take care not to use water-based solvents or alcohols for thinning.

- Thinner for ECS URETHANE
- The mixing ratio always depends on the type of spray application or dipping process.
- Depending on the desired flow behavior, the appropriate amount of diluent must be added to the concentrate.
- For spray application, a dilution in a ratio of 1:1 is recommended, which results in very good leveling behavior with a low layer thickness.
- For a higher layer thickness, a mixing ratio of 3 parts concentrate to 1 part thinner can be used.
- Attention: Water-based solvents and alcohols must not be used for dilution.

Products for the electronic industry



- Can
- Contents: 1 liter

| | |
|--------------------------|-------------------------------------------------------------|
| Item no. | WL83865 |
| Manufacturer | ECS |
| Manufacturer article no. | 776.L01.000 |
| GPSR manufacturer data | ECS AG Talstrasse 35 CH-8808 Pöfikon www.ecsag.com |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Incl. battery | no |
| ESD compliant | no |

