

Floor ramp, X-Lock, yellow, 500 x 90 x 10 mm, 1 piece



The 10 mm X-Lock floor ramp is designed to create a safe, angled ramp onto your ESD floor tiles. Each ramp is connected to a tile using X-Lock technology. We recommend using floor ramps at doorways and large transitions to avoid tripping hazards. A floor ramp is 500 mm long and can be connected almost seamlessly to an entire tile.

- Manufactured in the UK to ISO9001 standards
- REACH compliant PVC
- EN 1081, EN 1815 & EN6356
- Fire retardant - class Bfl s1
- Slip resistant
- Chemical resistant
- Reduces dust and noise
- Click-and-use installation
- Insulates the floor against cold and moisture

Item no.	WL83961
Manufacturer	ECOTILE
Manufacturer article no.	X59.601/1
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	500 mm
Width	90 mm
Height	10 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	yellow (RAL 1023)
Colour	yellow
Incl. battery	no
Connection system	X-Lock
Surface texture	flat
Strength	10 mm
Type of surface	floor ramp
ESD compliant	no

Other versions

Item no.	Strength
WL86003	5 mm
WL60309	7 mm
WL83961	10 mm