

ESD insert for Euro box 1 and 2, 15 recesses, 358 x 258 x 68 mm

Discover the ESD insert 358 x 258 x 68 mm at Weidinger.eu, the ideal solution for safe electronics production. This high-quality ESD thermoformed insert from Licefa, item number 2425976, offers optimum protection for sensitive electronic components. Made from dissipative polystyrene (PS) in elegant black, it guarantees a conductivity value in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms.

With external dimensions of 358 x 258 x 68 mm and 15 practical recesses (90 x 40 x 23 mm each), the insert fits perfectly into Euro boxes 1 and 2. The clever reversible stacking system and integrated recessed grip make handling and storage considerably easier.

This ESD insert is the perfect addition for your electronics production to organize and protect components safely and efficiently. Trust in the quality of Licefa and optimize your production processes with this reliable solution. Visit Weidinger.eu for more information and order today!

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- ESD deep-drawn inlay
- External dimensions 358 x 258 x 68 (L x W x H)
- Recesses: 15 (90x40x23 mm)
- Suitable for Euro boxes 1 and 2
- Reversible stacking
- Recessed grip

Item no.	WL85630
Alternative article name	T2-100-6-10
Manufacturer	LICEFA
Manufacturer article no.	2425976
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzflen www.licefa.de
Length	358 mm
Width	258 mm
Height	68 mm
Sales unit	1 piece

Content unit	1 piece
Length (recess)	90 mm
Width (recess)	40 mm
Height (recess)	23 mm
Number of recesses	15
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4 - <1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Length (recess)	Width (recess)	Height (recess)	Number of recesses
WL85643	35 mm	35 mm	15 mm	35
WL85657	57 mm	46 mm	15 mm	20
WL85644	80 mm	35 mm	20 mm	15
WL85630	90 mm	40 mm	23 mm	15
WL85645	90 mm	50 mm	20 mm	12
WL85637	189 mm	35 mm	41 mm	7