

ESD insert for Euro box 3 and 4, 60 grooves, 552 x 352 x 17 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. Measuring 552 x 352 x 17 mm and with 60 indentations, this insert offers optimum protection for sensitive electronic components. Made of dissipative polystyrene (PS), it ensures a conductivity value in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, which effectively prevents static discharges.

The insert has an elegant black finish and fits perfectly into Euro boxes in sizes 3 and 4. Easy handling is guaranteed thanks to the practical reversible stacking and the integrated recessed grip. The recesses measuring 63 x 21 x 7 mm provide sufficient space for safe storage and organization of your components.

With item number 2425988, this accessory is an indispensable component for any electronics production facility that values safety and efficiency. Rely on the quality of Licefa and optimize your production processes with this high-quality ESD insert.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 552 x 352 x 17 (L x W x H)
- Recesses: 60 (63 x 21 x 7)
- Reversible stacking
- Recessed handle
- Suitable for Euro boxes 3 and 4

Item no.	WL85636
Alternative article name	T2-106-6-10
Manufacturer	LICEFA
Manufacturer article no.	2425988
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzufen www.licefa.de
Length	552 mm
Width	352 mm
Height	17 mm
Sales unit	1 piece
Content unit	1 piece

Length (recess)	63 mm
Width (recess)	21 mm
Height (recess)	7 mm
Number of recesses	60
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Length (recess)	Width (recess)	Height (recess)	Number of recesses
WL85666	26 mm	18 mm	15 mm	208
WL85658	50 mm	31 mm	10 mm	78
WL85635	57 mm	30 mm	7 mm	40
WL85648	59 mm	51 mm	34 mm	24
WL85636	63 mm	21 mm	7 mm	60
WL85649	77 mm	59 mm	34 mm	20
WL85653	85 mm	65 mm	17 mm	21
WL85654	94 mm	65 mm	35 mm	21
WL85655	107 mm	47 mm	22 mm	27
WL85659	112 mm	106 mm	35 mm	12
WL85646	135 mm	50 mm	10 mm	50
WL85647	145 mm	15 mm	10 mm	42
WL85633	154 mm	80 mm	37 mm	12
WL85632	170 mm	155 mm	36 mm	6
WL85656	224 mm	90 mm	20 mm	7
WL85693	238 mm	102 mm	52 mm	6
WL85638	255 mm	135 mm	50 mm	4
WL85631	278 mm	233 mm	36 mm	2
WL85639	295 mm	155 mm	55 mm	3