ESD insert for Euro box 3 and 4, 4 wells, 550 x 350 x 55 mm

Discover the ESD insert 550 x 350 x 55 mm from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. This high-quality insert made of dissipative polystyrene (PS) offers optimum protection against electrostatic discharge and is ideal for use in size 3 and 4 Euro boxes. With a dissipative conductance of >1 x 10^4 to <1 x 10^{11} ohms, it guarantees reliable safety for sensitive electronic components.

The insert comes in elegant black and has four practical recesses (255 x 135 x 50 mm) that allow for safe and organized storage. Thanks to the reversible stacking system, flexible use and space-saving storage is guaranteed. With external dimensions of 550 x 350 x 55 mm, it fits perfectly into your existing systems.

The article number 2425992 makes it easy for you to order at Weidinger.eu. Trust in the quality of Licefa and protect your electronic components effectively and efficiently.
- Material: dissipative PS (polystyrene)
- Conductance: (dissipative >1 x 10^4 to <1 x 10^{11} Ohm)
- Color: black
- External dimensions: 550 x 350 x 55 (L x W x H)
- Recesses: 4 (255 x 135 x 50)
- Reversible stacking
- Suitable for Euro boxes 3 and 4

Item no.	**WL85638**
Alternative article name	T2-108-6-10
Manufacturer	LICEFA
Manufacturer article no.	2425992
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.licefa.de
Length	550 mm
Width	350 mm
Height	55 mm
Sales unit	1 piece
Content unit	1 piece
Length (recess)	255 mm
Width (recess)	135 mm
Height (recess)	50 mm

Number of recesses	4
Colour	black
Typical surface resistance (Rpp)	dissipativ >1 x 10^4 - <1 x 10^{11} Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Length (recess)	Width (recess)	Height (recess)	Number of recesses
WL85666	26 mm	18 mm	15 mm	208
WL85658	50 mm	31 mm	10 mm	78
WL85635	57 mm	30 mm	7 mm	40
WL85648	59 mm	51 mm	34 mm	24
WL85636	63 mm	21 mm	7 mm	60
WL85649	77 mm	59 mm	34 mm	20
WL85653	85 mm	65 mm	17 mm	21
WL85654	94 mm	65 mm	35 mm	21
WL85655	107 mm	47 mm	22 mm	27
WL85659	112 mm	106 mm	35 mm	12
WL85646	135 mm	50 mm	10 mm	50
WL85647	145 mm	15 mm	10 mm	42
WL85633	154 mm	80 mm	37 mm	12
WL85632	170 mm	155 mm	36 mm	6
WL85656	224 mm	90 mm	20 mm	7
WL85693	238 mm	102 mm	52 mm	6
WL85638	**255 mm**	**135 mm**	**50 mm**	**4**
WL85631	278 mm	233 mm	36 mm	2
WL85639	295 mm	155 mm	55 mm	3