ESD insert for Euro box 1 and 2, 50 wells, 355 x 255 x 28 mm

Discover the ESD insert 355 x 255 x 28 mm from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. This high-quality insert offers 50 recesses with a diameter of 22 x 20 mm and is ideal for the safe storage of sensitive electronic components. Made of dissipative polystyrene (PS) in elegant black, it ensures reliable protection against electrostatic discharge. The conductivity is in the dissipative range of >1 x 10^4 to <1 x 10^{11} ohms, which ensures optimum dissipation of static charges.

With external dimensions of 355 x 255 x 28 mm, the insert fits perfectly into size 1 and 2 Euro crates, allowing flexible integration into existing storage and transport systems. The article number 2425997 facilitates quick identification and ordering. This ESD insert is the ideal solution for companies that value the protection of their electronic components and at the same time strive for efficient organization of their working environment.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative >1 x 10^4 to <1 x 10^{11} Ohm)
- Color: black
- External dimensions: 355 x 255 x 28 (L x W x H)
- Recesses: 50, diameter 22 x 20 mm
- Suitable for Euro boxes 1 and 2

Item no.	**WL85640**
Alternative article name	T2-110-6-10
Manufacturer	LICEFA
Manufacturer article no.	2425997
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.licefa.de
Length	355 mm
Width	255 mm
Height	28 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	22 mm
Height (recess)	20 mm
Number of recesses	50
Colour	black

Typical surface resistance (Rpp)	dissipativ >1 x 10^4 - <1 x 10^{11} Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	**50**	**22 mm**	**20 mm**
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm