

ESD insert for Euro box 1 and 2, 35 wells, 350 x 255 x 73 mm

Discover the ESD insert 350 x 255 x 73 mm at Weidinger.eu - the ideal solution for the safe storage and transportation of sensitive electronic components. This high-quality insert from Licefa offers 35 precise recesses with a diameter of 35 x 37 mm, which ensure optimum protection against electrostatic discharge (ESD). Made from dissipative polystyrene (PS) in elegant black, it offers a conductivity value in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms.

The ESD insert is specially designed for Euroboxes 1 and 2 and enables space-saving storage thanks to its reversible stacking. Thanks to the practical recessed grip, easy and safe transportation is guaranteed. With external dimensions of 350 x 255 x 73 mm, it fits perfectly into your existing warehouse logistics. The article number 2426001 makes it easy for you to order quickly at Weidinger.eu. Rely on the quality and functionality of this ESD insert to make your electronics production efficient and safe.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions 350 x 255 x 73 (L x W x H)
- Recesses: 35, diameter 35 x 37 mm
- Reversible stacking
- Recessed handle
- Suitable for Euro boxes 1 and 2

Item no.	WL85642
Alternative article name	T2-112-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426001
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzufen www.licefa.de
Length	350 mm
Width	255 mm
Height	73 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	35 mm
Height (recess)	37 mm

Products for the electronic industry



Number of recesses	35
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm