ESD insert for Euro box 3 and 4, 20 wells, 555 x 355 x 47 mm

Discover the high-quality ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. Measuring 555 x 355 x 47 mm, this tray offers 20 wells, each measuring 77 x 59 x 34 mm, and is ideal for the safe storage of sensitive electronic components. Made of dissipative polystyrene (PS) in elegant black, it guarantees optimum protection against electrostatic discharge. The conductivity value is in the dissipative range of >1 x 10^4 to <1 x 10^{11} ohms, which ensures reliable dissipation of static charges.

The ESD insert is compatible with Euro boxes of sizes 3 and 4 and offers easy handling and space-saving storage thanks to the practical recessed grip and the option of reversible stacking. With item number 2426029, this product is the perfect addition for your electronics production to organize components safely and efficiently. Trust in the quality of Licefa and optimize your production processes with this well thought-out solution.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative >1 x 10^4 to <1 x 10^{11} Ohm)
- Color: black
- External dimensions: 555 x 355 x 47 (L x W x H)
- Recesses: 20, 77 x 59 x 34 mm
- Recessed grip
- Reversible stacking
- Suitable for Euro boxes 3 and 4

Item no.	**WL85649**
Alternative article name	T2-36-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426029
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.licefa.de
Length	555 mm
Width	355 mm
Height	47 mm
Sales unit	1 piece
Content unit	1 piece
Length (recess)	77 mm

Width (recess)	59 mm
Height (recess)	34 mm
Number of recesses	20
Colour	black
Typical surface resistance (Rpp)	dissipativ >1 x 10^4 - <1 x 10^{11} Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Length (recess)	Width (recess)	Height (recess)	Number of recesses
WL85666	26 mm	18 mm	15 mm	208
WL85658	50 mm	31 mm	10 mm	78
WL85635	57 mm	30 mm	7 mm	40
WL85648	59 mm	51 mm	34 mm	24
WL85636	63 mm	21 mm	7 mm	60
WL85649	**77 mm**	**59 mm**	**34 mm**	**20**
WL85653	85 mm	65 mm	17 mm	21
WL85654	94 mm	65 mm	35 mm	21
WL85655	107 mm	47 mm	22 mm	27
WL85659	112 mm	106 mm	35 mm	12
WL85646	135 mm	50 mm	10 mm	50
WL85647	145 mm	15 mm	10 mm	42
WL85633	154 mm	80 mm	37 mm	12
WL85632	170 mm	155 mm	36 mm	6
WL85656	224 mm	90 mm	20 mm	7
WL85693	238 mm	102 mm	52 mm	6
WL85638	255 mm	135 mm	50 mm	4
WL85631	278 mm	233 mm	36 mm	2
WL85639	295 mm	155 mm	55 mm	3