

ESD insert for Euro box 1 and 2, 56 recesses, 352 x 252 x 17 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. This high-quality insert with item number 2426073 offers optimum protection for sensitive electronic components. Made of dissipative polystyrene (PS), it ensures safe dissipation of electrostatic charges with a dissipative conductance of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms.

The insert is elegantly black and measures 352 x 252 x 17 mm. It has 56 recesses with a diameter of 30 x 15 mm, which are ideal for safely storing small components. A practical recessed grip makes handling easier.

Compatibility with size 1 and 2 Euro boxes is particularly advantageous, allowing flexible integration into existing storage systems. This ESD insert is the perfect solution for anyone who values safety and efficiency in electronics production.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 352 x 252 x 17 (L x W x H)
- Recesses: 56, diameter 30 x 15 mm
- Recessed grip
- Suitable for Euro boxes 1 and 2

Item no.	WL85668
Alternative article name	T2-70-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426073
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.licefa.de
Length	352 mm
Width	252 mm
Height	17 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	30 mm
Height (recess)	15 mm

Products for the electronic industry



Number of recesses	56
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm