

ESD insert for Euro box 1 and 2, 35 indentations, 352 x 252 x 14 mm



Discover the ESD insert from Licefa, available at [Weidinger.eu](https://www.weidinger.eu), which has been specially developed for safe electronics production. Measuring 352 x 252 x 14 mm, this tray offers 35 wells with a diameter of 37.5 x 6 mm, ideal for the organized storage of sensitive components. Made from dissipative polystyrene (PS) in elegant black, it ensures a conductivity value in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, providing optimum protection against electrostatic discharge.

The ESD insert is compatible with Euroboxes 1 and 2 and has a practical recessed grip for easy handling. With item number 2426077, it is an indispensable accessory for any electronics production facility that values safety and tidiness. Rely on the quality of Licefa and optimize your work processes with this well thought-out solution.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 352 x 252 x 14 (L x W x H)
- Recesses: 35, diameter 37.5 x 6 mm
- Recessed grip
- Suitable for Euro boxes 1 and 2

Item no.	WL85670
Alternative article name	T2-72-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426077
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.liceфа.de
Length	352 mm
Width	252 mm
Height	14 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	37.5 mm
Height (recess)	6 mm
Number of recesses	35
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm

WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm

