

ESD insert for Euro box 1 and 2, 20 recesses, 352 x 252 x 17 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for safe electronics production. This insert with item number 2426079 offers optimum protection for sensitive components thanks to its dissipative polystyrene material. With a dissipative conductance of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, it guarantees reliable ESD protection. The insert comes in elegant black and measures 352 x 252 x 17 mm, making it perfect for Euro boxes of sizes 1 and 2.

The 20 recesses with a diameter of 50 x 15 mm provide sufficient space for the safe storage and organization of your components. A practical recessed grip facilitates handling and transportation. This ESD insert is the ideal solution for anyone who values safety and organization in electronics production. Place your trust in the quality of Licefa and protect your sensitive components effectively.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 352 x 252 x 17 (L x W x H)
- Recesses: 20, diameter 50 x 15 mm
- Recessed grip
- Suitable for Euro boxes 1 and 2

Item no.	WL85671
Alternative article name	T2-73-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426079
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.liceфа.de
Length	352 mm
Width	252 mm
Height	17 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	50 mm
Height (recess)	15 mm

Number of recesses	20
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm