

ESD insert for Euro box 1 and 2, 12 wells, 352 x 252 x 17 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for safe electronics production. This high-quality insert with item number 2426081 offers optimum protection against electrostatic discharge and is ideal for use in Euro boxes sizes 1 and 2.

Made of dissipative polystyrene (PS) in elegant black, the insert with a dissipative conductance of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms ensures reliable protection for sensitive electronic components. The external dimensions of 352 x 252 x 17 mm and the 12 recesses with a diameter of 67 x 15 mm provide sufficient space for the safe storage and organization of your components. A practical recessed grip makes handling and transportation easier.

This ESD insert is the perfect addition to your Euro boxes and ensures efficient and safe storage in your electronics production. Rely on the quality of Licefa and optimize your work processes with this indispensable accessory.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 352 x 252 x 17 (L x W x H)
- Recesses: 12, diameter 67 x 15 mm
- Recessed grip
- Suitable for Euro boxes 1 and 2

Item no.	WL85672
Alternative article name	T2-74-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426081
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.liceфа.de
Length	352 mm
Width	252 mm
Height	17 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	67 mm
Height (recess)	15 mm

Products for the electronic industry



Number of recesses	12
Colour	black
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm