

## ESD insert for Euro box 1 and 2, 320 wells, 352 x 252 x 20 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for electronics production. This insert offers optimum protection for sensitive components thanks to its dissipative polystyrene material. With a dissipative conductance of  $>1 \times 10^4$  to  $<1 \times 10^{11}$  ohms, it guarantees reliable ESD protection. The insert comes in elegant black and measures 352 x 252 x 20 mm, making it perfect for Euro boxes of sizes 1 and 2.

The 320 recesses with a diameter of 7 x 15 mm provide sufficient space for the safe storage of small components. A practical recessed grip makes handling easier, while the reversible stacking system enables space-saving storage. This ESD insert, item number 2426085, is the ideal solution for safe and efficient organization in electronics production. Place your trust in the quality of Licefa and effectively protect your components from electrostatic discharge.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative  $>1 \times 10^4$  to  $<1 \times 10^{11}$  Ohm)
- Color: black
- External dimensions: 352 x 252 x 20 (L x W x H)
- Recesses: 320, diameter 7 x 15 mm
- Recessed grip
- Reversible stacking
- Suitable for Euro boxes 1 and 2

<b>Item no.</b>	<b>WL85674</b>
Alternative article name	T2-76-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426085
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzufen www.licefa.de
Length	352 mm
Width	252 mm
Height	20 mm
Sales unit	1 piece
Content unit	1 piece
Diameter (recess)	7 mm
Height (recess)	15 mm

Products for the electronic industry



Number of recesses	320
Colour	black
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

## Other versions

Item no.	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
<b>WL85674</b>	<b>320</b>	<b>7 mm</b>	<b>15 mm</b>