

ESD insert for Euro box 1 and 2, 35 recesses, 352 x 252 x 34 mm

Discover the ESD insert from Licefa, available at Weidinger.eu, which has been specially developed for safe electronics production. Measuring 352 x 252 x 34 mm, this tray offers 35 wells with a diameter of 35 x 30 mm, ideal for the organized storage of sensitive components. Made from dissipative polystyrene (PS), it ensures a conductivity value in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, providing optimum protection against electrostatic discharge. The black insert is equipped with a practical recessed grip and enables reversible stacking, which facilitates handling and storage. It is compatible with Euro boxes 1 and 2, which underlines its versatility. The article number 2426120 makes ordering easier. This ESD insert is the perfect solution for anyone who values safety and organization in electronics production.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- External dimensions: 352 x 252 x 34 (L x W x H)
- Recesses: 35, diameter 35 x 30 mm
- Recessed grip
- Reversible stacking
- Suitable for Euro boxes 1 and 2

item number	WL85690
Alternative item description	T2-95-6-10
manufacturer	LICEFA
manufacturer item number	2426120
GPSR manufacturer information	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.liceфа.de
length	352 mm
width	252 mm
height	34 mm
order unit	1 piece
content unit	1 piece
Diameter (recess)	35 mm
Height (recess)	30 mm
Number of recesses	35

Colour	black
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
material	plastic
ESD safe	yes

Other versions

item number	Number of recesses	Diameter (recess)	Height (recess)
WL85673	6	85 mm	15 mm
WL85672	12	67 mm	15 mm
WL85671	20	50 mm	15 mm
WL85690	35	35 mm	30 mm
WL85642	35	35 mm	37 mm
WL85669	35	35.5 mm	15 mm
WL85670	35	37.5 mm	6 mm
WL85677	48	16 mm	15 mm
WL85640	50	22 mm	20 mm
WL85668	56	30 mm	15 mm
WL85676	70	15 mm	40 mm
WL85678	80	17 mm	14 mm
WL85674	320	7 mm	15 mm