

ESD drawer insert for surface-mounted enclosure AFS 340/62, 9 compartments á 75 x 105 x 53 mm



Discover the ESD drawer insert from Licefa at Weidinger.eu, which has been specially developed for the safe storage of sensitive electronic components. With item number 2426266, this drawer insert offers nine practical compartments, each measuring 75 x 105 x 53 mm. Made of dissipative polystyrene (PS) in elegant black, it guarantees optimum protection against electrostatic discharge. The conductivity value is in the dissipative range of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, which ensures reliable dissipation of static charges.

This drawer liner is compatible with the ESD drawer 8162043 and the ESD surface-mounted cabinet plug-in system type AFS 340/62 (article number 8900121). It is the ideal solution for anyone who wants to store their electronic components safely and in an organized manner. Benefit from the high-quality workmanship and the well thought-out layout, which enables efficient use of the storage space. Perfect for use in electronics production, where safety and organization are top priorities.

- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black
- Suitable for ESD drawer 8162043
- suitable for ESD surface-mounted cabinet plug-in system: Cabinet type AFS 340/62: 8900121
- Compartments: 9
- Compartment size: 75 x 105 x 53 mm

Item no.	WL85731
Alternative article name	TE 9-60-6-10
Manufacturer	LICEFA
Manufacturer article no.	2426266
GPSR manufacturer data	LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzufen www.liceфа.de
Length	225 mm
Height	53 mm
Sales unit	1 piece
Content unit	1 piece
Length (compartment)	75 mm
Width (compartment)	105 mm
Height (compartment)	53 mm
Colour	black
Material	PS
Incl. battery	no
Typical surface resistance (Rpp)	dissipativ $>1 \times 10^4$ - $<1 \times 10^{11}$ Ohm
Material storage boxes	plastic
ESD compliant	yes

Other versions

Item no.	Length (compartment) x Width (compartment)
WL85704	50 mm x 47 mm
WL85731	75 mm x 105 mm

WL85724

75 mm x 160 mm

WL85712

116 mm x 160 mm

