

ESD assortment box SOK 166, black, 295 x 166 x 39 mm



Discover the ESD assortment box 166 at Weidinger.eu - the ideal solution for the safe storage of sensitive electronic components. Made of dissipative polystyrene (PS), this assortment box offers reliable protection against electrostatic discharge. With a dissipative conductance of $>1 \times 10^4$ to $<1 \times 10^{11}$ ohms, it ensures the safety of your components.

The assortment box in elegant black impresses with its compact dimensions: it measures 303x192x46 mm on the outside and 295x166x39 mm on the inside. These dimensions make it perfect for organizing and storing smaller items. The article number 8120365 makes it easy for you to order at Weidinger.eu.

Thanks to Licefa's robust construction, the assortment box is durable and hard-wearing. It is an indispensable accessory for any electronics production facility that values quality and safety. Rely on the ESD assortment box 166 for efficient and safe storage of your components.

- Assortment box 166
- Material: dissipative PS (polystyrene)
- Conductance: (dissipative $>1 \times 10^4$ to $<1 \times 10^{11}$ Ohm)
- Color: black,
- LxWxH, outside: 303x192x46 mm (height UT: 32 mm, height OT: 14 mm)

- LxWxH, inside: 295x166x39 mm
- Internal dimensions 295 x 166 x 39 mm

| | |
|----------------------------------|--|
| Item no. | WL85860 |
| Alternative article name | SOK 166, 028/014 ESD |
| Manufacturer | LICEFA |
| Manufacturer article no. | 8120365 |
| GPSR manufacturer data | LICEFA GmbH & Co.KG Lemgoer Strasse 11 DE-32108 Bad Salzuflen www.liceфа.de |
| Length | 303 mm |
| Width | 192 mm |
| Height | 46 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Colour | black |
| Inner length | 295 mm |
| Inner width | 166 mm |
| Inner height | 39 mm |
| Incl. battery | no |
| Typical surface resistance (Rpp) | dissipativ $>1 \times 10^4 - <1 \times 10^{11}$ Ohm |
| Material storage boxes | plastic |
| ESD compliant | yes |

Other versions

| Item no. | Inner height |
|----------|--------------|
| WL85859 | 21 mm |
| WL85860 | 39 mm |