

Floor ramp, X-Lock, yellow, 500 x 90 x 5 mm, 1 piece



The 5 mm X-Lock floor ramp is designed to create a safe, angled ramp onto your ESD floor tiles. Each ramp is connected to a tile using X-Lock technology. We recommend using floor ramps at doorways and large transitions to avoid tripping hazards. A floor ramp is 500 mm long and can be connected almost seamlessly to an entire tile.

- Manufactured in the UK to ISO9001 standards
- REACH compliant PVC
- EN 1081, EN 1815 & EN6356
- Fire retardant - class Bfl s1
- Slip resistant
- Chemical resistant
- Reduces dust and noise
- Click-and-use installation
- Insulates the floor against cold and moisture

Products for the electronic industry



Item no.	WL86003
Manufacturer	ECOTILE
Manufacturer article no.	X55.601
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	500 mm
Width	90 mm
Height	5 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	yellow (RAL 1023)
Colour	yellow
Incl. battery	no
Connection system	X-Lock
Surface texture	flat
Strength	5 mm
Type of surface	floor ramp
ESD compliant	no

Other versions

Item no.	Strength
WL86003	5 mm
WL60309	7 mm
WL83961	10 mm