

ESD earthing tile, X-Lock, light gray, 497 x 497 x 5 mm, 1 piece



The 5 mm ESD X-Lock earthing tile is used every 50 square meters. The earthing tile can be connected to the earth via an earthing cable to an earthing plug or earthing rail in accordance with the installation instructions.

Note: Please observe the installation instructions for ecotile floor tiles. This is available under "Documents" > "Download technical data sheet".

- Manufactured in the UK to ISO9001 standards
- REACH compliant PVC
- 497mm x 497mm x 5mm
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between 3.0×10^4 Ohm/m² and 3×10^6 Ohm
- Contact resistance is between 3.6×10^5 Ohm and 9.5×10^5 Ohm
- Fire-retardant - class Bfl s1
- Slip-resistant
- Resistant to chemicals

- Reduces dust and noise
- Click-and-use installation
- Insulates the floor against cold and moisture

Item no.	WL86066
Model	ECOTILE-16.1043LG
Manufacturer	ECOTILE
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	497 mm
Width	497 mm
Height	5 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	light gray (RAL 7004)
Colour	light grey
Connection system	X-Lock
Surface texture	flat
Strength	5 mm
Type of surface	floor tile
ESD compliant	yes

Other versions

Item no.	Strength
WL86066	5 mm
WL60420	7 mm
WL86197	10 mm