

ZeroSmog Guard Light Kit solder fume extraction, 74W, 230V, with hose & ALFA nozzle, single-user filter unit



Breathe easy with the Weller ZeroSmog Guard, the quietest filter unit on the market. This first-class filter unit ensures that your workplace remains clean, quiet and fresh. Thanks to its compact design, it can be easily stored under the workbench without taking up valuable space. Your health comes first here. You can concentrate on your work and work in a quiet environment without having to worry about air quality. Improve your working environment and protect your well-being with this efficient and reliable solder fume extraction solution. Show less

- Ensures excellent air quality through highly efficient filtering of soldering particles and gases with a large filter surface (H13 HEPA particle filter, activated carbon).
- The lowest noise level on the market ensures a healthy, pleasant and comfortable working environment.
- User-friendly thanks to quick and easy change of pre-filter and main filter.
- Saves space with a compact design under the workbench, ideal for use by one person.

- The robust blower ensures sufficient suction pressure throughout the filter's service life and thus a high volume flow for effective capture of all fumes.
- Entry-level single-user filter unit for 1 user, set with accessories
- 74 W, 230 V
- Filtration at the highest level - for clean and healthy air
- Highly effective particle and gas filtration
- Odor removal during soldering
- Constant suction pressure over the entire service life of the filter thanks to powerful fan
- Easily accessible on/off switch
- ESD-safe
- Compatible with Weller Easy-Click 60 hose system

| | |
|--------------------------|---|
| Item no. | WL86209 |
| Manufacturer | WELLER |
| Manufacturer article no. | FT91024699 |
| GPSR manufacturer data | WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu |
| Length with packaging | 590 mm |
| Width with packaging | 410 mm |
| Height with packaging | 610 mm |
| Scope of delivery | ZeroSmog Guard Light - 230 V, 1 x main filter (HEPA H13 and activated carbon), 5 x ePM1-75 % pre-filters, 1 x ALFA nozzle, 1 x OF15 hose, 1 x table clamp |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Power | 74 W |
| Voltage | 220 – 240 V |
| Vacuum (max.) | 2700 Pa |
| Conveying capacity | 100 m ³ /h |
| Sound level | 65 – 70 dBA |
| Volume flow rate (max.) | 100 m ³ /h |
| Filter type | main filter, prefilter |
| ESD compliant | yes |