

ESD magazine trolley, loading area 1000 x 600 mm



Electrically conductive design. Welded tubular steel and sectional steel, electrically conductive powder-coated, slate gray RAL 7015. Screw and plug-in construction. Base made of electrically conductive wood-based panel to DIN 68765, light gray. 2 swivel castors and 2 fixed castors, wheels with TPE-ESD tires (thermoplastic elastomer), electrically conductive, hubs with precision deep groove ball bearings. Maximum comfort: Very low starting, rolling and swivel resistance. Quiet running on level floors. Non-marking tires (non-marking). Brakes on the swivel castors.

- Total load capacity (kg): 300
- Load surface length (mm): 1000
- Shelf width (mm): 600
- Shelf height (mm): 206
- Overall length (mm): 1250
- Overall width (mm): 600
- Overall height (mm): 910
- Tires: TPE-ESD

- Wheel size (mm): 125 x 32

Item no.	WL86985
Manufacturer	FETRA
Manufacturer article no.	91202
GPSR manufacturer data	fetra Fechtel Transportgeräte GmbH Industriestraße 17-21 DE-33829 Bogenhausen www.fetra.de
Length	1250 mm
Height	910 mm
Sales unit	1 piece
Content unit	1 piece
Colour	dark grey
Incl. battery	no
Tires	TPE
Length of the loading area	1000 mm
Width of the loading area	600 mm
ESD compliant	yes