

Bit socket, insulated, with 3/8" drive, with holding function, TX 20 x 55 mm

VDE 3/8" bit socket with holding function for particularly convenient screwing with reduced risk of screw loss when feeding to the workpiece. With increased safety thanks to the yellow insulation core, which becomes visible if the outer red VDE insulation layer is damaged. Unit-tested tool in accordance with IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.

- Unit-tested tool in accordance with IEC 60900 at 10,000 V for safe working up to 1,000 volts
- Extremely short and compact insulated 3/8" bit socket for easy working even in very tight spaces
- Increased safety thanks to 2-component insulation with yellow insulation core under red insulation outer layer
- The holding function holds screws securely on the tool
- Plastic coating protects surfaces from damage

Item no.	WL88318
Model	8740 B VDE HF TORX® Zyklus
Manufacturer	WERA
Manufacturer article no.	05004920001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	160 mm
Width	120 mm
Height	23 mm
Length with packaging	160 mm
Width with packaging	120 mm
Height with packaging	23 mm
Sales unit	1 piece
Content unit	1 piece
VDE	yes
Screw type	TX20

ESD compliant	no
Tool length	55 mm

Other versions

Item no.	Screw type
WL88318	TX20
WL88319	TX25
WL88320	TX27
WL88321	TX30
WL88322	TX40
WL88323	TX45