

## Bit socket, insulated, with 3/8" drive, with holding function, TX 27 x 55 mm



VDE 3/8" bit socket with holding function for particularly convenient screwing with reduced risk of screw loss when feeding to the workpiece. With increased safety thanks to the yellow insulation core, which becomes visible if the outer red VDE insulation layer is damaged. Unit-tested tool in accordance with IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.

- Unit-tested tool in accordance with IEC 60900 at 10,000 V for safe working up to 1,000 volts
- Extremely short and compact insulated 3/8" bit socket for easy working even in very tight spaces
- Increased safety thanks to 2-component insulation with yellow insulation core under red insulation outer layer
- The holding function holds screws securely on the tool
- Plastic coating protects surfaces from damage

Item no.	WL88320
Model	8740 B VDE HF TORX® Zyklus
Manufacturer	WERA
Manufacturer article no.	05004922001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg

www.wera.de

Length	56 mm
Width	22.8 mm
Height	22.8 mm
Length with packaging	56 mm
Width with packaging	22.8 mm
Height with packaging	22.8 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	yes
Screw type	TX27
ESD compliant	no
Tool length	55 mm

## Other versions

Item no.	Screw type
WL88318	TX20
WL88319	TX25
<b>WL88320</b>	<b>TX27</b>
WL88321	TX30
WL88322	TX40
WL88323	TX45