

Torque indicator, TX 25 x 5.0 Nm

Wera torque indicator with fixed torque for TORX® screws. Tamper-proof. The robust slip clutch guarantees a clearly audible and perceptible trigger signal when the set torque is reached and it is impossible to overtighten. The release torque is several times higher than the set tightening torque, meaning that for the most part no additional tools are required to loosen screw connections. The shape of the handle fills the entire hand well and the fingers lie in the softly rounded recessed grips. This ensures optimum, ergonomic power transmission.

- Cross grip is ideal for transferring controlled tightening and high loosening torques
- Error-free fastening thanks to non-overtightening slipping clutch and precise torque transmission
- Tamper-proof against changing the set value
- Particularly corrosion-resistant blade

Item no.	WL88350
Model	400 TX
Manufacturer	WERA
Manufacturer article no.	05005091001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	150 mm
Width	105 mm
Height	30 mm
Length with packaging	150 mm
Width with packaging	105 mm
Height with packaging	30 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
Screw type	TX25
ESD compliant	no
Torque	5 Nm

Other versions

Item no.	Screw type
WL88349	TX20
WL88350	TX25