

## VDE-insulated, self-adjusting open-end wrench, 10-13 x 7/16-1/2" x 155 mm



Unit-tested tool in accordance with IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V. The adjustable VDE open-end wrench automatically and continuously grips all hexagon sizes in the specified size range - metric and imperial. The integrated lever mechanism clamps the hexagon bolt or nut securely between the jaws, significantly reducing the risk of slipping and damage. The ratchet function ensures fast and continuous screwing without settling. By using the corner width prisms, a swing-back angle of just 30° can be achieved. The single-leg design in conjunction with the ratchet function and the corner width prism makes it possible to work even in tight installation spaces. Thanks to the 2-component plastic insulation, the adjustable Joker 6004 VDE has a comfortable grip. Safety is increased by the anti-slip protection at the front end of the handle. Additional protection is provided by the sliding function for contactless and safe opening of the non-insulated jaws.

- The adjustable Joker 6004 VDE covers all metric and imperial dimensions in the respective application area
- Unit-tested tool with insulated handles for safe working up to 1,000 volts with slip protection and sliding function for contactless and safe opening of the non-insulated jaws
- Automatic and stepless gripping of hexagon bolts and nuts
- Lever mechanism for gripping prevents slipping and damage
- With mechanical ratchet function for fast and continuous screwing without having to put the key down

Item no.	WL88793
Model	6004 Joker VDE S
Manufacturer	WERA
Manufacturer article no.	05020151001

Products for the electronic industry



## GPSR manufacturer data

WERA Werkzeuge GmbH  
Korzter Strasse 21-25  
DE-42349 Wuppertal-Cronenberg  
www.wera.de

Length	180 mm
Width	50 mm
Height	26 mm
Length with packaging	218 mm
Width with packaging	81 mm
Height with packaging	51 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	yes
ESD compliant	no
Tool length	155 mm

