

## Combination wrench, imperial, 1/4" x 105 mm



As installation spaces for screwdriving work are becoming increasingly tight, tools are required that enable users to work successfully in such situations. Tight installation spaces require additional attachment points for the tool. So can open-end wrenches be modified in such a way that the tool's contact points are increased? The combination of the 7.5° swiveled jaw and the double hexagon geometry doubles the contact points. With a repeated 180° rotation of the wrench around the longitudinal axis during screwdriving, there are four tightening options and nuts or screw heads can be "gripped" every 15°. The Joker 6003 with its clever jaw geometry significantly extends the range of applications in tight installation spaces. The Joker 6003 finds the respective starting point automatically, so to speak, after every turn. The slim yet robust ring side is angled at 15° to the tool axis. The high-quality surface coating ensures high and long-lasting corrosion protection. With Take it easy tool finder: color coding according to size.

- Particularly suitable for tight installation spaces
- The special jaw geometry extends the application possibilities of the tool
- The small return angle in the jaw "grabs" the screw every 15°
- Slim, 15° angled ring side
- With Take it easy tool finder: color coding according to size

|                          |                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------|
| Item no.                 | <b>WL88827</b>                                                                                 |
| Model                    | 6003 Joker                                                                                     |
| Manufacturer             | WERA                                                                                           |
| Manufacturer article no. | 05020220001                                                                                    |
| GPSR manufacturer data   | WERA Werkzeuge GmbH<br>Korzerter Strasse 21-25<br>DE-42349 Wuppertal-Cronenberg<br>www.wera.de |
| Length                   | 130 mm                                                                                         |
| Width                    | 50 mm                                                                                          |
| Height                   | 25 mm                                                                                          |
| Length with packaging    | 246 mm                                                                                         |

|                       |         |
|-----------------------|---------|
| Width with packaging  | 89 mm   |
| Height with packaging | 62 mm   |
| Sales unit            | 1 piece |
| Content unit          | 1 piece |
| Incl. battery         | no      |
| VDE                   | no      |
| ESD compliant         | no      |
| Tool length           | 105 mm  |
| Wrench size           | 1/4"    |

## Other versions

| Item no.       | Wrench size |
|----------------|-------------|
| WL88821        | 1/2"        |
| <b>WL88827</b> | <b>1/4"</b> |
| WL88825        | 3/4"        |
| WL88819        | 3/8"        |
| WL88804        | 5,5 mm      |
| WL88823        | 5/8"        |
| WL88818        | 5/16"       |
| WL88805        | 6 mm        |
| WL88806        | 7 mm        |
| WL88820        | 7/16"       |
| WL88807        | 8 mm        |
| WL88826        | 9 mm        |
| WL88822        | 9/16"       |
| WL88808        | 10 mm       |
| WL88809        | 11 mm       |
| WL88824        | 11/16"      |
| WL88810        | 12 mm       |
| WL88811        | 13 mm       |
| WL88812        | 14 mm       |
| WL88813        | 15 mm       |
| WL88814        | 16 mm       |

|         |       |
|---------|-------|
| WL88815 | 17 mm |
| WL88816 | 18 mm |
| WL88817 | 19 mm |
| WL88858 | 20 mm |
| WL88859 | 21 mm |
| WL88860 | 22 mm |
| WL88861 | 24 mm |
| WL88862 | 27 mm |
| WL88863 | 30 mm |
| WL88864 | 32 mm |
| WL88865 | 36 mm |