

## BTZ bit for slotted screws, 1.2 x 6.5 x 25 mm



Torsion zone into which kinetic energy is dissipated during peak loads. With softer BiTorsion zone to prevent the bit tip from twisting under high loads. This significantly increases the product service life. Tough and hard, for universal use. 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 holders.

- For slotted screws
- With BiTorsion zone to absorb peak loads
- Significantly reduces the risk of breakage, significantly extends the service life
- Tough, for universal use
- 1/4" hexagon drive (Wera connection series 1)

|                          |  |
|--------------------------|--|
| <b>Item no.</b>          | <b>WL89545</b>   |
| Model                    | 800/1 BTZ  |
| Manufacturer             | WERA   |
| Manufacturer article no. | 05056068001  |
| GPSR manufacturer data   | WERA Werkzeuge GmbH<br>Korzerter Strasse 21-25<br>DE-42349 Wuppertal-Cronenberg<br>www.wera.de |
| Length                   | 25 mm  |
| Width                    | 7 mm   |
| Height                   | 7 mm   |
| Length with packaging    | 58 mm  |
| Width with packaging     | 34 mm  |
| Height with packaging    | 15 mm  |
| Sales unit               | 1 piece  |

Products for the electronic industry



|                 |         |
|-----------------|---------|
| Content unit    | 1 piece |
| Bit length      | 25 mm   |
| VDE             | no      |
| ESD compliant   | no      |
| Blade width     | 6.5 mm  |
| Blade thickness | 1.2 mm  |

## Other versions

| Item no. | Blade width x Blade thickness |
|----------|-------------------------------|
| WL89543  | 5.5 mm x 0.8 mm               |
| WL89544  | 5.5 mm x 1 mm                 |
| WL89545  | 6.5 mm x 1.2 mm               |