

## BTZ bit for slotted screws, 1.2 x 6.5 x 25 mm



Torsion zone into which kinetic energy is dissipated during peak loads. With softer BiTorsion zone to prevent the bit tip from twisting under high loads. This significantly increases the product service life. Tough and hard, for universal use. 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 holders.

- For slotted screws
- With BiTorsion zone to absorb peak loads
- Significantly reduces the risk of breakage, significantly extends the service life
- Tough, for universal use
- 1/4" hexagon drive (Wera connection series 1)

<b>Item no.</b>	<b>WL89545</b>
Model	800/1 BTZ
Manufacturer	WERA
Manufacturer article no.	05056068001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	25 mm
Width	7 mm
Height	7 mm
Length with packaging	58 mm
Width with packaging	34 mm
Height with packaging	15 mm
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Incl. battery	no
Bit length	25 mm
VDE	no
ESD compliant	no
Blade width	6.5 mm
Blade thickness	1.2 mm

## Other versions

Item no.	Blade width x Blade thickness
WL89543	5.5 mm x 0.8 mm
WL89544	5.5 mm x 1 mm
<b>WL89545</b>	<b>6.5 mm x 1.2 mm</b>