BDC bit for slotted screws, 0.8 x 5.5 x 25 mm



Bits for slotted screws with tiny diamond particles on the bit tip. These ensure a secure fit in the screw, reduce the required contact pressure and reduce the risk of slipping. With torsion zone into which kinetic energy is dissipated during peak loads. This significantly increases the product service life. 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 holders.

- For slotted screws
- With BiTorsion zone to absorb peak loads
- Significantly reduces the risk of breakage, significantly extends the service life
- Diamond coating for a secure fit in the screw
- 1/4" hexagon drive (Wera connection series 1)

Item no.	**WL89551**
Model	800/1 BDC
Manufacturer	WERA
Manufacturer article no.	05056172001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	25 mm
Width	7 mm
Height	7 mm
Length with packaging	58 mm
Width with packaging	34 mm
Height with packaging	15 mm
Sales unit	1 piece

Content unit	1 piece
Bit length	25 mm
VDE	no
ESD compliant	no
Blade width	5.5 mm
Blade thickness	0.8 mm

Other versions

Item no.	Blade width x Blade thickness
WL89551	**5.5 mm x 0.8 mm**
WL89552	5.5 mm x 1 mm
WL89553	6.5 mm x 1.2 mm