# BTZ hexagon socket bit, 2 x 25 mm




BiTorsion bits for hexagon head screws with elastic torsion zone, into which kinetic energy is dissipated during peak loads. With softer BiTorsion zone to prevent the bit tip from twisting under high loads. This significantly increases the product service life. Extra-hard design. 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 holders.

- For hexagon socket screws
- With BiTorsion zone to cushion peak loads
- Significantly reduces the risk of breakage, significantly extends service life
- Tough, for universal use
- 1/4" hexagon drive (Wera connection series 1)

| **Item no.** | **WL89614** |
|---|---|
| Model | 840/1 BTZ |
| Manufacturer | WERA |
| Manufacturer article no. | 05056681001 |
| GPSR manufacturer data | WERA Werkzeuge GmbH<br>Korzerter Strasse 21-25<br>DE-42349 Wuppertal-Cronenberg<br>www.wera.de |
| Length | 25 mm |
| Width | 7 mm |
| Height | 7 mm |
| Length with packaging | 58 mm |
| Width with packaging | 34 mm |
| Height with packaging | 15 mm |
| Sales unit | 1 piece |

| | |
|---|---|
| Content unit | 1 piece |
| Bit length | 25 mm |
| VDE | no |
| ESD compliant | no |
| Hexagon socket | 2 mm |

## Other versions

| Item no. | Hexagon socket |
|---|---|
| WL89613 | 1.5 mm |
| **WL89614** | **2 mm** |
| WL89615 | 2.5 mm |
| WL89616 | 3 mm |
| WL89617 | 4 mm |
| WL89618 | 5 mm |
| WL89619 | 5.5 mm |
| WL89620 | 6 mm |