

Slotted bit, 0.6 x 4.5 x 50 mm



Tough-hard Wera bits for slotted screws, for universal use. 1/4" hexagon, suitable for DIN ISO 1173-F 6.3 holders.

- For slotted screws
- Tough-hard, for universal use
- 1/4" hexagon drive (Wera connection series 4)

| | |
|--------------------------|--|
| Item no. | WL89753 |
| Model | 800/4 Z |
| Manufacturer | WERA |
| Manufacturer article no. | 05059315001 |
| GPSR manufacturer data | WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de |
| Length | 50 mm |
| Width | 7 mm |
| Height | 6 mm |
| Length with packaging | 58 mm |
| Width with packaging | 34 mm |
| Height with packaging | 15 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Incl. battery | no |
| Bit length | 50 mm |
| VDE | no |
| ESD compliant | no |
| Blade width | 4.5 mm |
| Blade thickness | 0.6 mm |

Other versions

| Item no. | Blade width | Blade thickness | Bit length |
|----------------|---------------|-----------------|--------------|
| WL51597 | 3 mm | 0.5 mm | 50 mm |
| WL22853 | 3 mm | 0.5 mm | 70 mm |
| WL22854 | 3.5 mm | 0.6 mm | 70 mm |
| WL89760 | 3.5 mm | 0.6 mm | 152 mm |
| WL89752 | 4 mm | 0.5 mm | 50 mm |
| WL71953 | 4 mm | 0.8 mm | 50 mm |
| WL89764 | 4 mm | 0.8 mm | 70 mm |
| WL73439 | 4 mm | 0.8 mm | 89 mm |
| WL89761 | 4 mm | 0.8 mm | 152 mm |
| WL89753 | 4.5 mm | 0.6 mm | 50 mm |
| WL71800 | 4.5 mm | 0.6 mm | 89 mm |
| WL89754 | 5.5 mm | 0.8 mm | 50 mm |
| WL89755 | 5.5 mm | 1 mm | 50 mm |
| WL89765 | 5.5 mm | 1 mm | 70 mm |
| WL19121 | 5.5 mm | 1 mm | 89 mm |
| WL89762 | 5.5 mm | 1 mm | 152 mm |
| WL89756 | 6 mm | 1 mm | 50 mm |
| WL89757 | 6.5 mm | 1.2 mm | 50 mm |
| WL89766 | 6.5 mm | 1.2 mm | 70 mm |
| WL71801 | 6.5 mm | 1.2 mm | 89 mm |
| WL89763 | 6.5 mm | 1.2 mm | 152 mm |
| WL89758 | 8 mm | 1.2 mm | 50 mm |
| WL71802 | 8 mm | 1.2 mm | 89 mm |
| WL89759 | 8 mm | 1.6 mm | 50 mm |
| WL89767 | 8 mm | 1.6 mm | 89 mm |