

Slotted bit, 1.6 x 8 x 50 mm



Tough-hard Wera bits for slotted screws, for universal use. 1/4" hexagon, suitable for DIN ISO 1173-F 6.3 holders.

- For slotted screws
- Tough-hard, for universal use
- 1/4" hexagon drive (Wera connection series 4)

Item no.	WL89759
Model	800/4 Z
Manufacturer	WERA
Manufacturer article no.	05059345001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	50 mm
Width	8 mm
Height	8 mm
Length with packaging	59 mm
Width with packaging	38 mm
Height with packaging	23 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Bit length	50 mm
VDE	no
ESD compliant	no
Blade width	8 mm
Blade thickness	1.6 mm

Other versions

Item no.	Blade width	Blade thickness	Bit length
WL51597	3 mm	0.5 mm	50 mm
WL22853	3 mm	0.5 mm	70 mm
WL22854	3.5 mm	0.6 mm	70 mm
WL89760	3.5 mm	0.6 mm	152 mm
WL89752	4 mm	0.5 mm	50 mm
WL71953	4 mm	0.8 mm	50 mm
WL89764	4 mm	0.8 mm	70 mm
WL73439	4 mm	0.8 mm	89 mm
WL89761	4 mm	0.8 mm	152 mm
WL89753	4.5 mm	0.6 mm	50 mm
WL71800	4.5 mm	0.6 mm	89 mm
WL89754	5.5 mm	0.8 mm	50 mm
WL89755	5.5 mm	1 mm	50 mm
WL89765	5.5 mm	1 mm	70 mm
WL19121	5.5 mm	1 mm	89 mm
WL89762	5.5 mm	1 mm	152 mm
WL89756	6 mm	1 mm	50 mm
WL89757	6.5 mm	1.2 mm	50 mm
WL89766	6.5 mm	1.2 mm	70 mm
WL71801	6.5 mm	1.2 mm	89 mm
WL89763	6.5 mm	1.2 mm	152 mm
WL89758	8 mm	1.2 mm	50 mm
WL71802	8 mm	1.2 mm	89 mm
WL89759	8 mm	1.6 mm	50 mm
WL89767	8 mm	1.6 mm	89 mm