

## ESD torque screwdriver, fixed preset measured value, handle size 105 mm, 1.2 Nm x 1.2-3.0 Nm



Wera torque screwdriver. Reliable protection against electrostatic energy and associated damage. With torque value preset at the factory to the smallest scale value. For all applications where the same torque is required constantly and repeat accuracy is required. The torque value can be changed within the measuring range using an extra tool (re-calibration kit, can be ordered with code number 05137001001). Then check the set value with a commercially available torque tester. Unlimited loosening torque for loosening tight screws. Rapidaptor quick-change technology for lightning-fast bit changes. Suitable for bits with 1/4" external hexagon drive to DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173). Multi-component Kraftform handle with hard and soft zones for high working speeds and to protect the palm of the hand.

Please note: 1 Ncm = 0.01 Nm.

- Factory preset, adjustable Kraftform ESD torque screwdriver
- Electrostatic safe tool due to surface resistance of  $\leq 10^9$  ohms
- Kraftform handle for fast and ergonomic screwdriving
- For bits with 1/4" external hexagon drive
- With Rapidaptor quick-change chuck for bits with 1/4" external hex drive

Item no.	<b>WL90395</b>
Model	Kraftform 7461 ESD
Manufacturer	WERA
Manufacturer article no.	05074842001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	170 mm
Width	40 mm

Products for the electronic industry



Height	40 mm
Length with packaging	170 mm
Width with packaging	40 mm
Height with packaging	40 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Product series	Series 7400 ESD Kraftform
VDE	no
ESD compliant	yes
Torque (max.)	1.2 Nm