

Torque wrench with reversible ratchet, 10-50 Nm, 1/2" x 10-50 Nm



Click torque wrench in the unmistakable Wera design. Very robust design with high accuracy in accordance with DIN EN ISO 6789-1:2017-07. Easy setting and securing of the specified value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. For clockwise tightening and with reversible ratchet with 45 teeth.

- With 1/2" square drive, reversible ratchet, 45 teeth
- Simple setting and securing of the desired torque value with audible and tactile click when the scale values are reached
- Safely dosed force: the torque wrench releases audibly and perceptibly when the set value is reached
- Measuring range: 10-50 Nm; precision $\pm 3 \%$ in accordance with DIN EN ISO 6789-1:2017-07
- Ergonomic 2-component handle for clockwise tightening

| | |
|--------------------------|--|
| Item no. | WL90398 |
| Model | C 1 k-Torque C 1 |
| Manufacturer | WERA |
| Manufacturer article no. | 05075620001 |
| GPSR manufacturer data | WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de |
| Length | 395 mm |
| Width | 60 mm |
| Height | 60 mm |
| Length with packaging | 395 mm |
| Width with packaging | 60 mm |

Products for the electronic industry



| | |
|-----------------------|---------|
| Height with packaging | 60 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| VDE | no |
| ESD compliant | no |
| Torque (from) | 10 Nm |
| Torque (to) | 50 Nm |

Other versions

| Item no. | Torque (from) x Torque (to) |
|----------------|-----------------------------|
| WL90398 | 10 Nm x 50 Nm |
| WL90399 | 20 Nm x 100 Nm |
| WL90400 | 40 Nm x 200 Nm |
| WL90401 | 60 Nm x 300 Nm |
| WL90402 | 80 Nm x 400 Nm |