

Adjustable torque wrench for right-hand and left-hand tightening, 1/2", 20-100 Nm



Click torque wrench in the unmistakable Wera design. For right-hand and left-hand tightening. Very robust design with high accuracy in accordance with DIN EN ISO 6789-1:2017-07. Easy setting and securing of the specified value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. With captive square drive for changing direction. 1/2" square drive with nut lock.

- For clockwise and anticlockwise tightening thanks to smooth switching of the captive square drive
- Measuring range: 20-100 Nm; precision $\pm 3 \%$ in accordance with DIN EN ISO 6789-1:2017-07
- 45 teeth and 1/2" square drive with nut lock
- Easy setting and securing of the desired torque value with audible and tactile click when the scale values are reached
- Safely dosed force: the torque wrench releases audibly and perceptibly when the set value is reached

Item no.	WL90403
Model	C 2 Push R/L C 2 Push R/L
Manufacturer	WERA
Manufacturer article no.	05075625001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	450 mm
Width	60 mm
Height	60 mm
Length with packaging	450 mm

Width with packaging	60 mm
Height with packaging	60 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
ESD compliant	no
Torque	20 – 100 Nm

Other versions

Item no.	Torque (from) x Torque (to)
WL90403	20 Nm x 100 Nm
WL90404	40 Nm x 200 Nm