

Adjustable torque wrench for right-hand and left-hand tightening, 3/4", 200-1000 Nm



Click torque wrench in the unmistakable Wera design. For right-hand and left-hand tightening. Very robust design with high accuracy in accordance with DIN EN ISO 6789-1:2017-07. Easy setting and securing of the specified value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. With captive 3/4" square drive through for changing direction.

- For right-hand and left-hand tightening thanks to smooth switching of the captive throughsquare
- Measuring range: 200-1000 Nm; precision \pm 3 % in accordance with DIN EN ISO 6789-1:2017-07
- 45 teeth and 3/4" square drive
- Simple setting and securing of the desired torque value with audible and tactile click when the scale values are reached
- Safely dosed force: the torque wrench releases audibly and perceptibly when the set value is reached

Item no.	WL90406
Model	E 1 Push R/L E 1 Push R/L
Manufacturer	WERA
Manufacturer article no.	05075631001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	1350 mm
Width	130 mm
Height	120 mm
Length with packaging	1350 mm
Width with packaging	130 mm
Height with packaging	120 mm

Products for the electronic industry









04.11.2025



Sales unit	1 piece
Content unit	1 piece
VDE	no
ESD compliant	no
Torque (from)	200 Nm
Torque (to)	1000 Nm









