

Torque wrench for insertion tools, 9x12, 20-100 Nm



Click torque wrench in the unmistakable Wera design. Very robust design with high accuracy in accordance with DIN EN ISO 6789-1:2017-07. Easy setting and securing of the specified value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. For right-hand and left-hand tightening and with 9x12 mm square socket for holding the corresponding socket tools.

- With holder for interchangeable 9x12 mm insert tools.
- Simple setting and securing of the desired torque value with audible and tactile click when the scale values are reached
- Safely metered force: the torque wrench releases audibly and perceptibly when the set value is reached
- Measuring range: 20-100 Nm; precision $\pm 3\%$ in accordance with DIN EN ISO 6789-1:2017-07
- Ergonomic 2-component handle for right-hand and left-hand tightening

item number	WL90409
model	X 3 k-Torque X 3
manufacturer	WERA
manufacturer item number	05075653001
GPSR manufacturer information	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
length	410 mm
width	60 mm
height	60 mm
length with packaging	410 mm
width with packaging	60 mm
height with packaging	60 mm

order unit	1 piece
content unit	1 piece
VDE	no
ESD safe	no
Torque (from)	20 Nm
Torque (up to)	100 Nm

Other versions

item number	Torque (from) x Torque (up to)
WL90407	2.5 Nm x 25 Nm
WL90408	10 Nm x 50 Nm
WL90413	10 Nm x 100 Nm
WL90409	20 Nm x 100 Nm
WL90410	40 Nm x 200 Nm
WL90411	60 Nm x 300 Nm
WL90412	80 Nm x 400 Nm