

Preset, adjustable torque wrench for insert tools, 10 Nm, 9x12, 10-50 Nm



Torque wrench with preset torque value for all applications where the same torque is required constantly and repeat accuracy is required. The torque value can be changed within the measuring range. The robust release mechanism guarantees a clearly audible and perceptible release signal when the set torque is reached. Suitable for interchangeable insertion tools for right-hand and left-hand tightening thanks to the square socket. Pre-setting to a desired torque value within the specified measuring range that deviates from these values is possible on request.

- Preset click-type torque wrench in the unmistakable Wera design
- Safely metered force: when the set value is reached, the torque wrench releases audibly and perceptibly
- Preset torque can be changed in the test laboratory within the measuring range
- Measuring range: 10-50 Nm; precision $\pm 2\%$ in accordance with DIN EN ISO 6789-1:2017-07
- With square socket (9x12 mm) for interchangeable insertion tools; right and left-hand tightening

Item no.	WL90417
Model	XP 2 Custom XP 2
Manufacturer	WERA
Manufacturer article no.	05075671010
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	290 mm
Width	50 mm
Height	50 mm
Length with packaging	290 mm
Width with packaging	50 mm

Products for the electronic industry



Height with packaging	50 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	no
ESD compliant	no
Torque	10 – 50 Nm