

Preset, adjustable torque wrench for insertion tools, 20 Nm, 14x18, 20-250 Nm



Torque wrench with preset torque value for all applications where the same torque is required constantly and repeat accuracy is required. The torque value can be changed within the measuring range. The robust release mechanism guarantees a clearly audible and perceptible release signal when the set torque is reached. Suitable for interchangeable insertion tools for right-hand and left-hand tightening thanks to the square socket. Pre-setting to a desired torque value within the specified measuring range that deviates from these values is possible on request.

- Preset click-type torque wrench in the unmistakable Wera design
- Safely metered force: when the set value is reached, the torque wrench releases audibly and perceptibly
- Preset torque can be changed in the test laboratory within the measuring range
- Measuring range: 20-250 Nm; precision $\pm 2\%$ in accordance with DIN EN ISO 6789-1:2017-07
- With square socket (14 x18) for interchangeable insert tools; right and left-hand tightening

Item no.	WL90421
Model	XP 4 Custom XP 4
Manufacturer	WERA
Manufacturer article no.	05075673010
GPSR manufacturer data	WERA Werkzeuge GmbH Korzelter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	490 mm
Width	60 mm
Height	60 mm
Length with packaging	490 mm
Width with packaging	60 mm
Height with packaging	60 mm
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Incl. battery	no
VDE	no
ESD compliant	no
Torque	20 – 250 Nm

Other versions

Item no.	Torque (from) x Torque (to)
WL90415	2.5 Nm x 25 Nm
WL90417	10 Nm x 50 Nm
WL90419	15 Nm x 100 Nm
WL90421	20 Nm x 250 Nm