

Torque wrench, adjustable, reversible ratchet, torque lock function, 1/2", 40-200 Nm



Adjustable torque wrench for controlled clockwise tightening. With 1/2" square drive. The torque function can be deactivated (torque lock function) so that the tool can also be used for loosening. Simple setting and securing of the preset value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. Fine-toothed reversible ratchet with 45 teeth. The accuracy is $\pm 3\%$ in accordance with DIN EN ISO 6789-1:2017-07.

- With 1/2" square drive
- Torque lock function: the torque function can be deactivated so that the tool can also be used for loosening
- Extra Click: audible and tactile adjustment of the torque
- Torque wrench releases audibly and perceptibly
- Measuring range: 40-200 Nm; precision $\pm 3\%$ in accordance with DIN EN ISO 6789-1:2017-07

Item no.	WL90426
Model	Lock C 3 que Lock C 3
Manufacturer	WERA
Manufacturer article no.	05075692001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	540 mm
Width	60 mm
Height	60 mm
Length with packaging	540 mm
Width with packaging	60 mm
Height with packaging	60 mm
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Incl. battery	no
VDE	no
ESD compliant	no
Torque	40 – 200 Nm

