Torque wrench, adjustable, torque function, square drive-through (1/2"), right/left-hand tightening, 40-200 Nm



Adjustable torque wrench for controlled right-hand and left-hand tightening. With 1/2" square drive. The torque function can be deactivated (torque lock function) so that the tool can also be used for loosening. Simple setting and securing of the preset value. The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque is reached. Fine-toothed reversible ratchet with 45 teeth. The accuracy is ±3 % in accordance with DIN EN ISO 6789-1:2017-07.

- For right-hand and left-hand tightening
- Torque lock function: the torque function can be deactivated so that the tool can also be used for loosening
- With square drive-through (including patented nut lock)
- Extra Click: audible and tactile torque adjustment
- Torque wrench releases audibly and perceptibly

Item no.	**WL90429**
Model	Lock C 3 R/L Lock C 3 R/L
Manufacturer	WERA
Manufacturer article no.	05075695001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	540 mm
Width	60 mm
Height	60 mm
Length with packaging	540 mm
Width with packaging	60 mm
Height with packaging	60 mm
Sales unit	1 piece

Content unit	1 piece
VDE	no
ESD compliant	no
Torque	40 – 200 Nm