

Torque wrench with 1/4" square drive, 2-12 Nm, 1/4" x 2-12 Nm



Torque wrench with over-slip mechanism. Once the set torque value has been reached, the tool cannot be overtightened, preventing the application of excessive torque. Setting range from 2 to 12 Nm for controlled right-hand and left-hand tightening. Simple setting and securing of the preset value: The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. With torque lock function for use as a standard ratchet without torque function. Max. Max. breaking torque of the 1/4" square in accordance with DIN 3122. The return angle is only 5°, so that the ratchet can also be used in tight working situations. Can therefore also be used for turning angle applications.

- Slip-over release mechanism - the set torque value can therefore never be exceeded
- Torque lock function: The torque function can be switched off - tool can therefore also be used as a standard ratchet with high release torques and for defined rotation angle applications
- For controlled right-hand and left-hand tightening - tightening and loosening with and without torque
- Simple setting and securing of the desired torque value with audible and tactile engagement when the scale values are reached
- Only 30° release angle after reaching the target torque value

| | |
|--------------------------|--|
| Item no. | WL90430 |
| Model | Safe-Torque A 1 |
| Manufacturer | WERA |
| Manufacturer article no. | 05075800001 |
| GPSR manufacturer data | WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de |
| Length | 290 mm |
| Width | 50 mm |
| Height | 50 mm |

Products for the electronic industry



| | |
|-----------------------|-----------|
| Length with packaging | 290 mm |
| Width with packaging | 50 mm |
| Height with packaging | 50 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Incl. battery | no |
| VDE | no |
| ESD compliant | no |
| Torque | 2 – 12 Nm |