

## Torque wrench with 1/4" hexagon drive, 2-12 Nm, 2-12 Nm



Torque wrench with over-slip mechanism. Once the set torque value has been reached, the tool cannot be overtightened, preventing excessive torque from being applied. Setting range from 2 to 12 Nm for controlled right-hand and left-hand tightening. Simple setting and securing of the preset value: The audible and tactile click when the scale values are reached also makes it easier to set the desired torque value safely. With torque lock function for use as a standard ratchet without torque function. Can therefore also be used for torque angle applications. The return angle is only 5°, so that the ratchet can also be used in tight working situations.

- Slip-over release mechanism - the set torque value can therefore never be exceeded
- Torque lock function: The torque function can be switched off - tool can therefore also be used as a standard ratchet with high release torques and for defined rotation angle applications
- For controlled right-hand and left-hand tightening - tightening and loosening with and without torque
- Simple setting and securing of the desired torque value with audible and tactile engagement when the scale values are reached
- Only 30° release angle after reaching the target torque value

item number	WL90431
model	Safe-Torque A 2
manufacturer	WERA
manufacturer item number	05075801001
GPSR manufacturer information	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
length	290 mm
width	50 mm
height	50 mm
length with packaging	290 mm

width with packaging	50 mm
height with packaging	50 mm
order unit	1 piece
content unit	1 piece
VDE	no
ESD safe	no
Torque (from)	2 Nm
Torque (up to)	12 Nm